



# PCIe Cable

With crossover cabling, the connectors on either end of the PCIe x4 cable are identical. Each connector is equipped with a retractor allowing the connector to be locked into place. OSS-PCIe-CBL-x4



- PCIe x4 cable
- Available in 1m, 2m, 3m, 5m and 7m lengths

- PCI-SIG PCI Express Cable Specification Compliant
- Includes x4 PCIe lanes and side-band signals for:
  - Power-on
  - Reset
  - SM Bus (clock/data)
  - 100MHz Reference clock
  - Board Present
  - Wake

- Positive latching mechanism per the PCI-SIG specification
- Supports 10 Gbps full-duplex transfer rates

## TECHNICAL SPECIFICATIONS

### PCIe Cable

Cable Length	1m, 2m, 3m, 5m, 7m
Circuits (Loaded)	38
Gender	Male-Male
Lock to Mating Part	Yes
Material - Metal	Zinc Alloy
Packaging Type	Bag
Pitch - Mating Interface	

0.80mm (.031")

Single Ended	No
Waterproof / Dustproof	Yes

Wire Insulation Diameter	N/A
--------------------------	-----

Wire Size AWG	28
Wire/Cable Type	Round

### Electrical

Current - Maximum per Contact	1A
Shielded	Yes
Voltage - Maximum	30V DC



[www.onestopsystems.com](http://www.onestopsystems.com)